

# Quick Check®

## Barcode Verifier



### Features

- Special reflectometer mode
- "X" dimension determination
- Data buffer (code content dependent)
- Single Scan To Result (SSTR) menu
- Command code programming
- ANSI/CEN/ISO scan profile test method
- Instant "On-Screen" ISO/IEC grade
- ISO/IEC 10-scan grade averaging

<b>Dimensions</b>	
Height:	2.8 in. (7.1 cm)
Width:	4.3 in. (10.9 cm)
Length:	5.3 in. (13.5 cm)
<b>Mechanical</b>	
Weight:	16 oz. (454 g)
Power:	4 AA rechargeable NiCad batteries and AC charger
Case:	Lexan polycarbonate 141
Beeper:	A single beeper provides an audible valid/invalid signal and a triple beep on known out of spec codes
Display:	4 line X 20 character LCD
Keypad:	6-button, power, select (4 arrows)
LEDs:	5 tri-colored LEDs
<b>Environmental</b>	
Operating Temperature:	32° to 122° F (0° to 50° C)
Storage Temperature:	14° to 158° F (-20° to 70°C)
Relative Humidity:	5% to 95% Non-condensing
<b>Optical</b>	
Test Aperture:	Mouse: 3, 5, 6, 10, or 20 mil Pen: 5, 6, 10 mil Linear Imager: min. "X" dimension 5 mil Beam width: 5.25 in. (13.3cm)
Wavelength:	Visible: 660nm Infrared: 940nm
<b>Symbologies</b>	
EAN/UPC with addenda, Code 39 (1-49 characters), Interleaved 2 of 5 (2-78 characters), Codabar, Code 128 (1-70 characters), MSI (1-50 characters), Code 16K (individual rows), Code 49 (individual rows), Code 93, Code 11, Regular 2 of 5 (Discrete/Industrial 2 of 5), IATA 2 of 5 (Straight 2 of 5), Database look-up feature	
<b>Safety/Regulatory</b>	
FCC Class A, CE Certified	

**Please order using part number MC4615-0012 £1488 plus carriage**

*The kit includes,*

- Hard carry case
- Linear imager (as pictured)
- Display unit (as pictured)
- Power supply/charger
- Manuals
- Test codes

**More Control UK Ltd**  
**Unit 13 Clarke Road**  
**Mount Farm Industrial Estate**  
**Milton Keynes**  
**MK1 1LG**  
**01908 364555**